

## ニットーコン 材質 R (酸化チタン系) 規格表 F 型

形 式 名	端子 構造	公 称 静電容量 PF±10%	定格電圧		定格 KVA		最大値			寸法 (mm)			備考
			KV <sub>DC</sub>		(1MHZ)		HF <sub>OP</sub> KV	電流 (A)		D <sub>Φ</sub> ±10%	T ±3	H ±3	
			50°C	70°C	50°C	70°C		50°C	70°C				
RDF200C-S	S	500	25	20	300	200	30	55	46	200	47.0	79.0	
RDF200C-S	S	1000	25	20	300	200	30	60	55	200	35.0	67.0	
RDF200C-S	S	1500	25	20	180	120	30	62	56	200	29.0	61.0	
RDF200C-S	S	2000	20	17	180	120	25	63	57	200	26.0	58.0	
RF-140S	S	500	25	20	90	60	30	30	25	140	25.0	52.0	
RF-140S	S	600	25	20	90	60	30	32	26	140	23.0	50.0	
RF-140S	S	700	25	20	90	60	30	33	27	140	24.0	51.0	
RF-140S	S	800	25	20	90	60	30	34	28	140	24.0	51.0	
RF-140S	S	1000	21	17	90	60	25	35	30	140	22.0	49.0	
RF-140S	S	1500	13	10	90	60	15	30	25	140	19.0	46.0	
RF-140S	S	2000	8	7	67.5	45	9	35	30	140	18.0	45.0	
RF-140S	S	2500	7	6	67.5	45	7	35	30	140	17.0	44.0	
RF-110S	S	200	20	17	45	30	25	18	15	110	30.0	57.0	
RF-110S	S	300	25	20	90	60	30	25	20	110	27.0	54.0	
RF-110S	S	400	25	20	90	60	30	26	21	110	25.0	52.0	
RF-110S	S	500	13	11	30	20	16	21	17	110	18.0	49.0	
RF-110S	S	600	15	12	30	20	18	22	18	110	18.5	47.0	
RF-110S	S	700	12	10	30	20	14	22	18	110	17.5	46.0	
RF-110S	S	800	12	10	30	20	14	26	18	110	17.5	45.0	
RF-110S	S	1000	10	8	30	20	12	25	20	110	15.0	44.0	
RF-110S	S	1200	8	7	22	14	10	25	20	110	14.5	44.0	
RF-110S	S	1500	8	7	22	14	10	25	20	110	14.0	43.5	
RF-110S	S	2000	7	6	22	14	7	25	20	110	13.5	43.0	
RF-110S	S	2500	5	4	22	14	5	25	20	110	13.0	42.0	
RF-80S	S	100	13	11	22	14	16	13	11	80	26.5	40.0	
RF-80S	S	150	13	11	22	14	16	13	11	80	26.5	40.0	
RF-80S	S	200	15	12	30	20	18	16	13	80	20.5	33.5	
RF-80S	S	250	15	12	30	20	18	16	13	80	19.0	32.0	
RF-80S	S	300	15	12	30	20	18	17	14	80	17.5	30.5	
RF-80S	S	400	12	10	15	10	14	16	13	80	16.0	29.0	
RF-80S	S	500	12	10	15	10	14	16	13	80	15.0	28.5	
RF-80S	S	600	10	8	15	10	12	17	14	80	14.5	27.5	
RF-80S	S	700	10	8	15	10	12	18	15	80	13.8	27.5	
RF-80S	S	800	8	7	15	10	9	18	15	80	13.8	27.0	
RF-80S	S	1000	8	7	15	10	9	18	15	80	13.5	27.0	
RF-80S	S	1200	6	5	15	10	7	18	15	80	12.8	26.5	
RF-80S	S	1500	5	4	10	8	6	18	15	80	12.5	26.0	
RF-60S	S	100	12	10	15	10	14	10	8	60	22.0	31.0	
RF-60S	S	150	12	10	15	10	14	11	9	60	19.0	30.0	
RF-60S	S	200	12	10	15	10	14	12	10	60	18.0	28.5	
RF-60S	S	250	12	10	15	10	14	12	10	60	18.0	27.5	
RF-60S	S	300	10	8	7.5	5	12	12	10	60	16.5	26.0	
RF-60S	S	400	10	8	7.5	5	12	12	10	60	15.5	25.5	
RF-60S	S	500	6	5	7.5	5	7	13	11	60	14.0	24.0	
RF-60S	S	600	6	5	7.5	5	7	13	11	60	13.5	23.5	
RF-60S	S	700	6	5	7.5	5	7	13	11	60	13.5	23.0	
RF-60S	S	800	5	4	7.5	5	6	13	11	60	13.5	23.0	
RF-60S	S	1000	5	4	7.5	5	6	13	11	60	12.5	22.0	
RF-40S	S	50	10	8	6	4	12	6	5	40	21.5	35.0	
RF-40S	S	100	10	8	6	4	12	7	6	40	19.0	28.0	
RF-40S	S	150	10	8	6	4	12	8	7	40	13.5	25.0	
RF-40S	S	200	5	4	4.5	3	6	8	7	40	13.2	23.5	
RF-40S	S	250	5	4	4.5	3	6	8	7	40	13.2	22.5	
RF-40S	S	300	5	4	4.5	3	6	9	8	40	13.2	22.5	
RF-30S	S	50	5	4	3	2	6	5	4	30	15.0	28.0	
RF-30S	S	100	5	4	3	2	6	6	5	30	12.0	23.5	
RF-30S	S	150	5	4	3	2	6	7	6	30	10.0	23.0	
RF-30S	S	200	4	3	3	2	5	7	6	30	10.0	22.0	

※RoHS対応品に関しては別途ご相談ください。

## ニットーコン 材質 R (酸化チタン系) 規格表 E 型

形 式 名	端子 構造	公 称 静電容量 PF±10%	定格電圧		定格 KVA		最大値			寸法 (mm)			備考
			KV <sub>DC</sub>		(1MHZ)		HF <sub>0P</sub> KV	電流 (A)		D <sub>Φ</sub> ±10%	T ±3	H ±3	
			50°C	70°C	50°C	70°C		50°C	70°C				
RE-110S	S	400	11	8.5	10	6.5	2	13.5	11	110	7.0	32.0	
RE-110S	S	500	11	8.5	10	6.5	2	14.5	12	110	7.0	32.0	
RE-110S	S	600	11	8.5	10	6.5	2	16	13	110	7.0	32.0	
RE-110S	S	700	11	8.5	10	6.5	2	16	13	110	7.0	32.0	
RE-110S	S	800	8.5	7.0	10	6.5	2	17	14	110	4.0	29.0	
RE-110S	S	1000	8.5	7.0	10	6.5	2	17	14	110	3.5	28.5	
RE-110S	S	1200	6.0	5.0	10	6.5	2	18.5	15	110	3.5	28.5	
RE-110S	S	1500	6.0	5.0	10	6.5	2	19.5	16	110	2.5	27.5	
RE-110S	S	2000	6.0	5.0	10	6.5	2	21	17	110	2.5	27.5	
RE-80S	S	300	8.5	7.0	7	4.5	2	11	9	80	5.0	29.0	
RE-80S	S	400	8.5	7.0	7	4.5	2	12	10	80	5.0	29.0	
RE-80S	S	500	8.5	7.0	7	4.5	2	13.5	11	80	4.4	28.4	
RE-80S	S	600	8.5	7.0	7	4.5	2	13.5	11	80	4.4	28.4	
RE-80S	S	700	7.0	5.5	7	4.5	2	14.5	12	80	2.2	26.2	
RE-80S	S	800	7.0	5.5	7	4.5	2	14.5	12	80	2.2	26.2	
RE-80S	S	1000	7.0	5.5	7	4.5	2	16	13	80	2.1	26.1	
RE-80S	S	1200	6.0	5.0	7	4.5	2	16	13	80	1.8	25.8	
RE-80S	S	1500	6.0	5.0	7	4.5	2	17	14	80	1.5	25.5	
RE-60S	S	200	7.0	5.5	5	3.5	2	8.5	7	60	4.5	24.5	
RE-60S	S	250	7.0	5.5	5	3.5	2	9.5	8	60	4.5	24.5	
RE-60S	S	300	7.0	5.5	5	3.5	2	9.5	8	60	4.5	24.5	
RE-60S	S	400	6.0	5.0	5	3.5	2	11	9	60	2.8	22.8	
RE-60S	S	500	6.0	5.0	5	3.5	2	11	9	60	2.8	22.8	
RE-60S	S	600	6.0	5.0	5	3.5	2	12	10	60	2.4	22.4	
RE-60S	S	700	5.0	4.0	5	3.5	2	12	10	60	2.4	22.4	
RE-60S	S	800	5.0	4.0	5	3.5	2	12	10	60	1.8	21.8	
RE-60S	S	1000	5.0	4.0	5	3.5	2	12	11	60	1.8	21.8	
RE-50S	S	100	6.0	5.0	4	2.8	2	6.5	5.5	50	7.5	27.5	
RE-50S	S	150	6.0	5.0	4	2.8	2	8	6.5	50	7.5	27.5	
RE-50S	S	200	6.0	5.0	4	2.8	2	8	6.5	50	4.0	24.0	
RE-50S	S	250	6.0	5.0	4	2.8	2	9	7.5	50	4.0	24.0	
RE-50S	S	300	6.0	5.0	4	2.8	2	9	7.5	50	4.0	24.0	
RE-50S	S	400	5.0	4.0	4	2.8	2	10	8	50	2.2	22.2	
RE-50S	S	500	5.0	4.0	4	2.8	2	10	8	50	2.2	22.2	
RE-50S	S	600	5.0	4.0	4	2.8	2	11	9	50	2.2	22.2	
RE-40S	S	50	5.0	4.0	3	2	2	6	5	40	6.5	26.5	
RE-40S	S	100	5.0	4.0	3	2	2	6	5	40	6.5	26.5	
RE-40S	S	150	5.0	4.0	3	2	2	7	6	40	3.0	23.0	
RE-40S	S	200	5.0	4.0	3	2	2	7	6	40	3.0	23.0	
RE-40S	S	250	5.0	4.0	3	2	2	8.5	7	40	2.5	22.5	
RE-40S	S	300	5.0	4.0	3	2	2	8.5	7	40	2.5	22.5	
RE-40S	S	400	3.5	2.8	2.2	1.5	2	8.5	7	40	1.5	21.5	
RE-40S	S	500	3.5	2.8	2.2	1.5	2	8.5	7	40	1.5	21.5	
RE-30S	S	50	5.0	4.0	2	1	2	5	4	30	5.5	25.5	
RE-30S	S	100	5.0	4.0	2	1	2	5	4	30	3.2	23.2	
RE-30S	S	150	5.0	4.0	2	1	2	6	5	30	2.0	22.0	
RE-30S	S	200	5.0	4.0	2	1	2	6	5	30	2.0	22.0	
RE-30S	S	250	3.0	2.5	2	1	2	6	5	30	1.7	21.7	
RE-30S	S	300	3.0	2.5	2	1	2	6	5	30	1.7	21.7	
RE-30S	S	400	2.0	1.5	1	0.7	1	6	5	30	1.0	21.0	
RE-30S	S	500	2.0	1.5	1	0.7	1	6	5	30	1.0	21.0	
RE-20S	S	50	3.0	2.5	1.5	1	2	3	2.5	20	3.3	19.3	
RE-20S	S	100	3.0	2.5	1.5	1	2	3	2.5	20	2.0	18.0	
RE-20S	S	150	2.0	1.5	1.5	1	2	4	3	20	1.2	17.2	
RE-20S	S	200	2.0	1.5	1.5	1	2	4	3	20	1.0	17.0	

※RoHS対応品に関しては別途ご相談ください。